

# Bảng thông số sản phẩm

## Đặc điểm

# 3031\_2\_3M\_F\_G19

## Concept - 16AX 250V 2 Way Standard Switch Module with Fluorescent Locator



### Main

|                               |                                   |
|-------------------------------|-----------------------------------|
| Range                         | Concept                           |
| Product or component type     | Switch                            |
| Device presentation           | Mechanism                         |
| Device application            | Switch                            |
| Colour tint                   | White                             |
| Type of packing               | Plastic bag                       |
| Quantity per set              | 1                                 |
| Sale per indivisible quantity | 1                                 |
| Load type                     | Inductive: 0...250 W<br>Resistive |

### Complementary

|                              |   |
|------------------------------|---|
| Device mounting              | Flush   |
| Switch function              | 2-way   |
| Number of modules            | 1 module S  |
| Number of rocker             | 1   |
| Actuator                     | Rocker  |
| Range compatibility          | Concept   |
| Fixing mode                  | Clip-in   |
| Surface finish               | Glossy  |
| Surface treatment            | Untreated   |
| Rated current                | 16 AX at 250 V AC 50/60 Hz                          |
| Electrical durability        | 20000 cycles conforming to IEC 60669                |
| Connections - terminals      | 3 screw terminals                                   |
| Shape of screw head          | Cross slotted                                       |
| Clamping connection capacity | <= 4 mm <sup>2</sup> for rigid or stranded cable(s) |

|                       |                                       |
|-----------------------|---------------------------------------|
| Wire stripping length | 12 mm                                 |
| Local signalling      | Locator light (green)                 |
| Material              | PC: dolly<br>PC: base<br>PC: surround |
| Height                | 46 mm                                 |
| Width                 | 23 mm                                 |
| Depth                 | 33 mm                                 |
| Embedding depth       | 25 mm                                 |

## Environment

|                                       |           |
|---------------------------------------|-----------|
| Ambient air temperature for storage   | 0...60 °C |
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity                     | 0...95 %  |
| Standards                             | IEC 60669 |
| IP degree of protection               | IP20      |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| RECh Regulation            | <a href="#">RECh Declaration</a>  |
| RECh free of SVHC          | Yes   |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End of Life Information</a>   |