

Product datasheet

Specifications



S-Flexi - 10A 250V Bell switch - L size - White

F50BPM4_WE

Main

Range	S-Flexi
Product or component type	Bell press switch
Wiring device mounting	Flush
Switch function	Bell push switch
Switch application	Bell switch
Load type	Bell chime
Colour tint	White

Complementary

Rated current	10 A at 250 V AC 50/60 Hz
Number of gangs	1 gang horizontal/vertical
Material	PC (polycarbonate): wall
Clamping connection capacity	0.5...1.5 mm ² for solid or flexible cable(s)
Connections - terminals	Pillar terminals
Width	46.55 mm
Height	70.2 mm
Depth	34.97 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Standards	IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	26.0 g
Package 1 Height	3.0 cm
Package 1 width	4.0 cm

Package 1 Length	7.0 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	372.0 g
Package 2 Height	8.0 cm
Package 2 width	12.5 cm
Package 2 Length	18.0 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	120
Package 3 Weight	4214.0 g
Package 3 Height	21.0 cm
Package 3 width	27.0 cm
Package 3 Length	43.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information