


Product datasheet

Specifications



2 Gang Telephone Outlet with Shutter

KB32TS_AS

Main

Range of product	Vivace
Range	Vivace
Device short name	KB32
Product or component type	Telephone socket
Device presentation	Complete mechanism

Complementary

Number of gangs	2 gangs
Colour tint	Aluminium silver
Material	Polycarbonate: surround Polycarbonate: grid plate Polycarbonate: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing center	60.3 mm
Embedding depth	35 mm
Connections - terminals	Clamp terminal
Tightening torque	0.4 N.m
Width	87 mm
Height	87 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Weight	91.0 g
Package 1 Height	2.2 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	980.0 g
Package 2 Height	9.5 cm
Package 2 Width	15.0 cm
Package 2 Length	19.0 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Weight	9349.0 g
Package 3 Height	210.0 mm
Package 3 Width	315.0 mm
Package 3 Length	500.0 mm