

Bảng thông số sản phẩm

Thông số kỹ thuật



Electronic Key Card Time Delay Switch, Silver Bronze

A8431EKT_SZ

Main

Range	ZENcelo
Product or component type	Key card switch
Rated current	16 A at 240 V AC
Colour tint	Silver bronze

Complementary

Status LED	LED
Material	Polycarbonate: base Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: lenses
Load type	Incandescent 16 A Fluorescent 8 AX Motor 8 A
Device mounting	Surface Flush
Connections - terminals	Brass terminal
Clamping connection capacity	1 x 1...4 x 1 mm ² for solid stranded cable(s) 2 x 2.5 mm ² for solid stranded cable(s) 1 x 1.5...3 x 1.5 mm ² for solid stranded cable(s)
Width	70 mm
Height	120 mm
Depth	40.7 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	<= 2000 m
Ambient air temperature for storage	0...60 °C
Standards	IEC 60669-2-1
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	164.5 g
Package 1 Height	6.3 cm
Package 1 Width	8.8 cm
Package 1 Length	13.2 cm
Unit Type of Package 2	PAL
Number of Units in Package 2	240
Package 2 Weight	1194400.0 g
Package 2 Height	120 cm
Package 2 Width	60 cm
Package 2 Length	80 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	30
Package 3 Weight	4935.0 g
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Thay thế được đề xuất