

Product datasheet

Specifications



Zencelo - 250V 16A SINGLE 3 PIN UNI 2M SIZED SKT

84426MUES_WE_G19

Main

Range	ZENcelo
Product or component type	Power socket-outlet
Outlet poles configuration	2P + E universal
Load type	Inductive Resistive
Cover plate colour tint	White

Complementary

Device mounting	Flush Surface
Rated current	16 A at 250 V AC 50 Hz
Number of gangs	1 gang
Marking	L+N
Material	Polycarbonate base Polycarbonate cover
Connections - terminals	Screw terminals
Embedding depth	21.5 mm
Width	46 mm
Height	46.6 mm
Depth	30 mm

Environment

Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	0...95 %, non-condensing (storage) 10...95 %, non-condensing (operating)
Environmental characteristic	UV resistant indoor use
Operating altitude	2000 m
IP degree of protection	IP20
Product certifications	TISI
Standards	IEC 60884-1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Recommended replacement(s)