

Product datasheet

Specifications



Zencelo - 250V "PCU" 2 WAY CONTROL SW

8431SPCU_WE_G19

Main

| | |
|---------------------------|---|
| Range | ZENcelo |
| Product or component type | Message indicator |
| Switch function | 2-way |
| Switch application | Switch |
| Local signalling | Please clean up: indicator light, LED (green) |
| Colour tint | White |

Complementary

| | |
|--------------------------------|--|
| [Ue] rated operational voltage | 250 V AC 50/60 Hz |
| Material | Brass: metal parts Polycarbonate: base Polycarbonate: cover Polycarbonate: lenses |
| Connections - terminals | Folded terminal |
| Width | 23.2 mm |
| Height | 45.8 mm |
| Depth | 31.7 mm |

Environment

| | |
|---------------------------------------|--------------|
| Ambient air temperature for operation | -5...45 °C |
| Ambient air temperature for storage | 0...60 °C |
| Relative humidity | 0...95 % |
| Environmental characteristic | UV resistant |
| Operating altitude | <= 2000 m |
| IP degree of protection | IP20 |

Offer Sustainability

| | |
|--------------------------|-----------------------------------|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |

| | |
|-----------------------------------|---|
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |

Recommended replacement(s)