

# Bảng thông số sản phẩm

Thông số kỹ thuật



## Zencelo - 250V "PCU" COURTESY DISPLAY

8430SPCU\_WE\_G19

### Main

Range	ZENcelo
Product or component type	Message indicator
Local signalling	Please clean up: indicator light, LED (green)
Colour tint	White

### Complementary

Clamping connection capacity	1 x 1...4 x 1 mm <sup>2</sup> for solid stranded cable(s) 1 x 1.5...5 x 1.5 mm <sup>2</sup> for solid stranded cable(s) 1 x 2.5...3 x 2.5 mm <sup>2</sup> for solid stranded cable(s) 1 x 4...2 x 4 mm <sup>2</sup> for solid stranded cable(s)
[Ue] rated operational voltage	250 V AC 50/60 Hz
Material	Brass: metal parts Polycarbonate: base Polycarbonate: cover Polycarbonate: lenses
Connections - terminals	Folded terminal
Width	23.2 mm
Height	45.8 mm
Depth	31.7 mm

### Environment

Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant
Operating altitude	<= 2000 m
IP degree of protection	IP20

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes

<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Toxic heavy metal free</b>	Yes
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>

**Thay thế** được đề xuất