

Bảng thông số sản phẩm

Thông số kỹ thuật



ZENcelo -16AX 1 Gang Full-Flat Intermediate Switch - Silver Satin

E8431_I_SA

Main

Range	ZENcelo
Product or component type	Switch
Load type	Inductive Fluorescent lamp Incandescent lamp
Colour tint	Silver satin
Cover frame colour tint	Silver satin

Complementary

Device mounting	Surface Flush
Switch function	1-way
Rated current	20 A at 250 V AC 50/60 Hz 16 AX
Number of gangs	1 gang
Material	Polycarbonate + GF 20 %: grid plate Polycarbonate: base Polycarbonate: cover Polycarbonate: surround
Connections - terminals	Pillar terminals
Embedding depth	23.9 mm
Width	87 mm
Height	87 mm
Depth	32.1 mm

Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	GB 16915.1 IEC 60669-1 SS 227-1 BS EN 60669-1 MS IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	8.72 cm
Package 1 Length	8.72 cm
Package 1 Weight	141.47 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	15 cm
Package 2 Width	19 cm
Package 2 Length	8 cm
Package 2 Weight	1.332 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	13817.6 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Thay thế được đề xuất