

## Main

Range	ZENcelo
Product or component type	Telephone + data socket
Device application	Communication
Cover frame colour tint	Silver satin
Socket additional information	Shuttered

### Complementary

Complementary	
Rated current	1.5 A
Communication network category	Data: 6 Voice: 3
Insulation resistance	>= 200 mOhm
Contact resistance	1 μOhm
Number of gangs	2 gangs
Connector type	RJ11 RJ45
Material	Polycarbonate housing
Contacts material	Contact: phosphor bronze with gold plating IDC contact: phosphor bronze with nickel plating
AWG gauge	AWG 26AWG 22 (4 twisted pair cables)
Minimum return loss	23 dB
Device mounting	Flush Surface
Fixing mode	By screws M4 x 25 mm
Fixing center	60.3 mm
Width	87 mm
Height	87 mm
Depth	39 mm
Embedding depth	30.6 mm

#### **Environment**

**Dielectric strength** 1000 V for 60 s at 60 Hz

035 °C
095 %
No UV resistant
ASTMD4566-98 TIA/EIA-568-B.2-1

# **Packing Units**

<u> </u>	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	8.72 cm
Package 1 Length	8.72 cm
Package 1 Weight	129.41 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	1.235 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	12852.8 g

### Offer Sustainability

Onor Guotamasmity	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Recommended replacement(s)