



### Main

Range	ZENcelo
Product or component type	Telephone + data socket
Device application	Communication
Socket additional information	Shuttered
Colour tint	Silver bronze

### Complementary

Communication network category	Voice: 3 Data: 6
Insulation resistance	>= 200 mOhm
Number of gangs	2 gangs
Contacts material	Contact: phosphor bronze with gold plating IDC contact: phosphor bronze with nickel plating
Material	Polycarbonate plastic part
Device mounting	Flush Surface
Width	87 Mm
Height	87 Mm
Depth	36 Mm
Embedding depth	30.2 Mm

### Environment

AWG gauge	AWG 34...AWG 23 (4 twisted pair cables)
Dielectric strength	1000 V for 60 s at 60 Hz
Ambient air temperature for operation	0...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Standards	ASTMD4566-98 TIA/EIA-568-B.2-1

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

Product Life Status : **Commercialised**