

Product datasheet

Specifications



ZENcelo - 2 Gang Telephone + Data Outlet Cat 6 (OS)

E8432TDRJS/6-OS

! Discontinued on: 01 November 2020

! Discontinued

Main

Range	ZENcelo
Product or component type	Telephone + data socket
Device application	Communication
Colour tint	White

Complementary

Communication network category	Voice: 3 Data: 6
Insulation resistance	≥ 200 mOhm
Number of gangs	2 gangs
Contacts material	Contact: phosphor bronze with gold plating IDC contact: phosphor bronze with nickel plating
Material	Polycarbonate plastic part
Device mounting	Flush Surface
Width	87 mm
Height	87 mm
Depth	36 mm
Embedding depth	30.2 mm

Environment

AWG gauge	AWG 34...AWG 23 (4 twisted pair cables)
Dielectric strength	1000 V for 60 s at 60 Hz
Ambient air temperature for operation	0...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Standards	ASTMD4566-98 TIA/EIA-568-B.2-1

Packing Units

Package 1 Weight	103.690 kg
Package 1 Height	1.000 mm
Package 1 Width	1.000 mm
Package 1 Length	1.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)