

Bảng thông số sản phẩm

Thông số kỹ thuật



10A 2G SOCKET, SILVER SATIN

E84426U2_SA_G19

Main

Range	ZENcelo
Product or component type	Power socket-outlet
Outlet poles configuration	2P
Load type	Resistive
Cover frame colour tint	Silver satin
Cover plate colour tint	Grey

Complementary

Device mounting	Surface Flush
Rated current	10 A at 250 V AC 50 Hz
Number of gangs	2 gangs
Material	Polycarbonate base Polycarbonate grid plate Polycarbonate surround Brass contact plate Polycarbonate cover
Connections - terminals	Clamps terminal
Width	87 mm
Height	87 mm
Depth	27 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	GB 2099.1 IEC 60884-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	8.7 cm
Package 1 Width	8.7 cm
Package 1 Length	2.7 cm
Package 1 Weight	0.001 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Thay thế được đề xuất