

# Bảng thông số sản phẩm

Thông số kỹ thuật



## 16A 250V UNI 3 PIN 2 GANG SOCKET SA

E84426UEST2RSA\_G19

### Main

Range	ZENcelo
Product or component type	Power socket-outlet
Socket additional information	Shuttered
Outlet poles configuration	2P + E American
Load type	Resistive
Cover frame colour tint	Silver satin
Cover plate colour tint	Grey

### Complementary

Device mounting	Flush Surface
Rated current	16 A at 250 V AC 50 Hz
Number of gangs	2 gangs
Material	Brass metal parts Steel metal parts PC base PC cover Nylon shutter
Connections - terminals	Folded terminal without pressure plate
Width	147 mm
Height	87 mm
Depth	26 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	IEC 60884-1

### Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>REACH free of SVHC</b>	Yes
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Toxic heavy metal free</b>	Yes
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>

Thay thế được đề xuất