

Bảng thông số sản phẩm

Thông số kỹ thuật



Zencelo - 1 Gang International socket

E84426_16TS_WE_G19

Main

Range	ZENcelo
Product or component type	Power socket-outlet
Socket additional information	Shuttered
Load type	Resistive
Cover frame colour tint	White
Cover plate colour tint	Grey

Complementary

Device mounting	Flush Surface
Rated current	16 A at 250 V AC 50 Hz
Number of gangs	1 gang
Material	Polycarbonate base Brass metal parts Nylon + GF shutter Polycarbonate cover Steel metal parts
Connections - terminals	Brass rod terminals
Width	87 mm
Height	87 mm
Depth	29 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Operating altitude	2000 m
Standards	IEC 60884-1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Thay thế được đề xuất