

Bảng thông số sản phẩm

Thông số kỹ thuật



16A 250V UNI 3 PIN 1 GANG SOCKET SA

E84426UESTR_SZ_G19

Main

Range	ZENcelo
Product or component type	Power socket-outlet
Outlet poles configuration	2P + E American
Load type	Resistive
Colour tint	Silver bronze
Cover frame colour tint	Silver satin

Complementary

Device mounting	Surface Flush
Rated current	16 A at 250 V AC 50 Hz
Number of gangs	1 gang
Material	Brass metal parts Steel metal parts PC base PC cover Nylon shutter
Connections - terminals	Folded terminal without pressure plate
Width	147 mm
Height	87 mm
Depth	26 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	IEC 60884-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	2.9 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	85 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	808 g
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	31 cm
Package 3 Length	50 cm
Package 3 Weight	6380 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Thay thế được đề xuất