

Product datasheet

Specifications



MX shunt trip, GoPact MCCB 125, 110/415VAC 50/60Hz

G12SHT415AC

Main

| | |
|------------------------------|--------------------------|
| Range of product | GoPact MCCB |
| Product or component type | Voltage release |
| Device short name | MX |
| Device application | Control |
| Range compatibility | GoPact (GoPact MCCB 125) |
| Voltage release type | Shunt trip |
| [Uc] control circuit voltage | 110...415 V AC 50/60 Hz |

Complementary

| | |
|--------------------------------------|----------------------|
| Threshold tripping voltage | 0.7...1.1 Un opening |
| Max supply pick-up power consumption | 5 VA |
| Response time | 25 ms |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.5 cm |
| Package 1 Width | 8.5 cm |
| Package 1 Length | 4.8 cm |
| Package 1 Weight | 0.09 kg |

Offer Sustainability

| | |
|----------------------------|--|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration |
| RoHS exemption information | Yes |

WEEE The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

PVC free

Yes

Recommended replacement(s)