

Product datasheet

Specifications



Auxiliary contact, GoPact MCCB 125/200/250, 1 NO/NC contact type, circuit breaker status OF/SD

G12-25AUX240

Main

Range of product	GoPact MCCB
Product or component type	Auxiliary contact
Device short name	OF and SD
Device application	Breaker status monitoring
Range compatibility	GoPact (GoPact MCCB 125) GoPact (GoPact MCCB 200) GoPact (GoPact MCCB 250)
Signal contacts composition	1 NO/NC

Complementary

Local signalling	ON/OFF indication for open/close Trip indicator for voltage release indication Trip indicator for electrical fault
Mounting mode	By screws
[I _{th}] conventional free air thermal current	6 A
[U _e] rated operational voltage	240 V AC
[I _e] rated operational current	AC-12: 6 A at 12 V AC 50/60 Hz AC-12: 6 A at 24 V AC 50/60 Hz AC-12: 6 A at 48 V AC 50/60 Hz AC-12: 6 A at 110 V AC 50/60 Hz AC-12: 6 A at 240 V AC 50/60 Hz AC-14: 6 A at 12 V AC 50/60 Hz AC-14: 6 A at 24 V AC 50/60 Hz AC-14: 6 A at 48 V AC 50/60 Hz AC-14: 6 A at 110 V AC 50/60 Hz AC-14: 6 A at 240 V AC 50/60 Hz DC-12: 6 A at 12 V DC DC-12: 5 A at 24 V DC DC-12: 1 A at 48 V DC DC-12: 0.5 A at 110 V DC DC-12: 0.25 A at 220 V DC
Mechanical durability	10000 cycles
Auxiliary connection terminal	Pre-wired 0.5 mm ²
Cable length	500 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 cm

Package 1 Width	8.5 cm
Package 1 Length	4.8 cm
Package 1 Weight	0.06 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

Recommended replacement(s)