

# Product datasheet

Specifications



## MX shunt trip, GoPact MCCB 400/800, 240VAC 50/60Hz

G40-80SHT240AC

### Main

|                              |  |
|------------------------------|--|
| Range of product             | GoPact MCCB  |
| Product or component type    | Voltage release                                      |
| Device short name            | MX   |
| Device application           | Control  |
| Range compatibility          | GoPact (GoPact MCCB 400)<br>GoPact (GoPact MCCB 800) |
| Voltage release type         | Shunt trip   |
| [Uc] control circuit voltage | 240 V AC 50/60 Hz                                    |

### Complementary

|                                      |                      |
|--------------------------------------|----------------------|
| Threshold tripping voltage           | 0.7...1.1 Un opening |
| Max supply pick-up power consumption | 5 VA                 |
| Response time                        | 25 ms                |

### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 6.5 cm  |
| Package 1 Width              | 8.5 cm  |
| Package 1 Length             | 4.8 cm  |
| Package 1 Weight             | 0.11 kg |

### Offer Sustainability

|                            |  |
|----------------------------|--|
| REACH Regulation           | <a href="#">REACH Declaration</a>                |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes  |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>           |
| RoHS exemption information | Yes  |

**WEEE** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

PVC free

Yes

Recommended replacement(s)