

Product datasheet

Specifications



Surface/DIN Mount 24 H Time Switch With Reserve

CCT15101

Main

Product Or Component Type	Mechanical time switch
Number Of Channels	1
Function Available	Manual time changeover

Complementary

Device Application	Building
Load Type	LED lamp 200 VA Compact fluorescent lamp 200 VA
Cycle Duration	24 h
Minimum Interval Duration	15 min
Type Of Setting	Manual time changeover
Power Consumption In Va	1.5 VA
Maximum Switching Current	16 A - 230 V AC pf = 1 4 A - 230 V AC pf = 0.6
[Ue] Rated Operational Voltage	230...240 V AC at 50/60 Hz
Backup Time	24 h
Mounting Support	DIN rail Surface mount
9 Mm Pitches	4
Colour Tint	Grey
Connections - Terminals	Screw terminals: 1...2.5 mm ²
Width	72 mm
Height	72 mm
Depth	51 mm

Environment

Ambient Air Temperature For Operation	-20...45 °C
Ip Degree Of Protection	IP20

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.5 cm

Package 1 Width	8.05 cm
Package 1 Length	8.05 cm
Package 1 Weight	180 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	48
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	9400 g
Unit Type Of Package 3	P12
Number Of Units In Package 3	1152
Package 3 Height	105 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	235 kg